



Gree Performance Masking Tape

R - 63

Product Description

Masking Paper Tape has characteristics of high temperature resistance, chemical solvent resistance, high adhesion, easy to tear, soft and easy to tear without residual glue. Widely used in painting, decoration, electronics and other industries.

Typical Physical Properties

Properties	Values	Test method
Material Type	Crepe Paper	
Adhesive	Natural Rubber	
Total Thickness	0.145mm – 0.15mm (145µm-150 µm)	PSTC-133 / ASTM D 3652
Adhesion to Steel	6N/25mm	PSTC-101 / ASTM D 3330
Initial Tack	6#	GB/T 4852-2002
Tensile Strength	60 N/25mm	PSTC-131 / ASTM D 3759
Elongation	6%	PSTC-131 / ASTM D 3759
Holding power	10H	PSTC-107 / ASTM D 3654

Storage & Shelf Life

12 months when stored at 23±2°C (73°F) / 50% relative humidity out of direct sunlight.

Application Technique

Clean the surface well with dry cloth.

Ensure surface is free from grease, oil, stains and dust.

Apply pressure after applying the tape to get better bonding.

Sizes

1550mm X 2000 Meters

All technical information and data mentioned above are only test values from RATCs laboratory, they shall not be considered as specification standards or guarantee values. The user is responsible for determining whether Gree product is fit for specific purposes or applications by conducting suitability testing, before placing a purchase order.

